Version 3.1

Revision Date 10/01/2023

Print Date 08/06/2024

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP 50 HEAVY DUTY FOAMING DEGREASER_NET 160Z_12CT

Material number : 15001C

Manufacturer or supplier's details

Company	:	Zep Inc.
Address	:	11627 - 178 Street Edmonton, Alberta T5S 1N6 Canada
Telephone	:	Compliance Services - 877-428-9937

Emergency telephone numbers

For SDS Information	:	Compliance Services - 877-428-9937
For a Medical Emergency	:	877-541-2016 Toll Free - All Calls Recorded
For a Transportation	:	CHEMTREC: 800-424-9300 - All Calls Recorded.
Emergency		

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a liquefied gas
Colour	amber
Odour	characteristic

GHS Classification

Flammable aerosols	: Category 1
Gases under pressure	: Liquefied gas
Skin corrosion	: Category 1
Serious eye damage	: Category 1
Skin sensitisation	: Sub-category 1B
Carcinogenicity	: Category 2

GHS label elements

sion 3.1	Revision Date 10/01/2023	Print Date 08/06/20
Hazard pictograms		
	Flame Gas cylinder Health h	hazard Exclamation mark
Signal word	: Danger	
Hazard statements	 H222 Extremely flammable aero H280 Contains gas under presso H315 Causes skin irritation. H317 May cause an allergic skin H319 Causes serious eye irritation H351 Suspected of causing canonal 	ure; may explode if heated. n reaction. ion.
Precautionary statements	 Prevention: P201 Obtain special instructions P202 Do not handle until all safe and understood. P210 Keep away from heat, hot and other ignition sources. No si P211 Do not spray on an open ff P251 Do not pierce or burn, even P261 Avoid breathing dust/ fume P264 Wash skin thoroughly after P272 Contaminated work clothin the workplace. P280 Wear protective gloves/ pr protection/ face protection. Response: P302 + P352 IF ON SKIN: Wash P305 + P351 + P338 IF IN EYES for several minutes. Remove con easy to do. Continue rinsing. P308 + P313 IF exposed or cond attention. P333 + P313 If skin irritation or r advice/ attention. P362 + P364 Take off contamina reuse. Storage: P410 + P412 Protect from sunlig temperatures exceeding 50 °C/ Disposal: P501 Dispose of contents/contail regulation. 	ety precautions have been in surfaces, sparks, open flam imoking. flame or other ignition source in after use. e/ gas/ mist/ vapours/ spray ir handling. ing should not be allowed out rotective clothing/ eye h with plenty of water. S: Rinse cautiously with wa intact lenses, if present and cerned: Get medical advice rash occurs: Get medical sists: Get medical advice/ ated clothing and wash it be ght. Do not expose to 122 °F.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Version 3.1

Revision Date 10/01/2023 Print Date 08/06/2024

Chemical name	CAS-No.	Concentration [%]
sodium dodecylbenzenesulfonate	25155-30-0	>= 5 - < 10
2-(2-butoxyethoxy)ethanol	112-34-5	>= 1 - < 5
d-limonene	5989-27-5	>= 1 - < 5
propane	74-98-6	>= 1 - < 5
butane	106-97-8	>= 1 - < 5
Amides, coco, N,N-bis(hydroxyethyl)	68603-42-9	>= 1 - < 5
tetrapotassium pyrophosphate	7320-34-5	>= 1 - < 5
Sulfonic acids, C14-16-alkane hydroxy and C14- 16-alkene, sodium salts	68439-57-6	>= 1 - < 5
benzyl alcohol	100-51-6	>= 1 - < 5
2,2'-iminodiethanol	111-42-2	>= 0.1 - < 1

SECTION 4. FIRST AID MEASURES

General advice	:	Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended. Get medical attention immediately.
If inhaled	:	If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	:	If skin irritation persists, call a physician. Remove contaminated clothing and shoes. Wash off immediately with plenty of water for at least 15 minutes. Wash contaminated clothing before re-use.
In case of eye contact	:	Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
If swallowed	:	Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. DO NOT induce vomiting unless directed to do so by a physician or poison control center. Take victim immediately to hospital.
Most important symptoms and effects, both acute and delayed	:	Chronic effects are delayed and symptoms may not be observed during an exposure. Effects are dependent on exposure (dose, concentration, contact time). Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash. Causes serious eye irritation. May cause an allergic skin reaction. Review section 2 of SDS to see all potential hazards. Causes skin irritation.
Notes to physician	:	Treat symptomatically. Symptoms may be delayed.

Version 3.1

Revision Date 10/01/2023 Print Date 08/06/2024

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical Water spray jet
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	Carbon dioxide (CO2) Carbon monoxide Sulphur oxides Smoke
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	 Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains, inform respective authorities.
Methods and materials for containment and cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal.

Version 3.1

Revision Date 10/01/2023 Print Date 08/06/2024

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	 Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Always replace cap after use. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Do not breathe vapours or spray mist.
Conditions for safe storage	 BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. No smoking. Keep in a dry, cool and well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
Materials to avoid	: Do not freeze. Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2-(2-butoxyethoxy)ethanol	112-34-5	TWA (Inhalable fraction and vapor)	10 ppm	ACGIH
propane	74-98-6	TWA	1,000 ppm	CA AB OEL
		TWA	1,000 ppm	CA BC OEL
		TWAEV	1,000 ppm	CA QC OEL
			1,800 mg/m3	
		TWA	1,000 ppm	CA ON OEL
butane	106-97-8	TWA	1,000 ppm	CA AB OEL
		TWA	600 ppm	CA BC OEL
		STEL	750 ppm	CA BC OEL
		TWAEV	800 ppm	CA QC OEL
			1,900 mg/m3	
		STEL	1,000 ppm	ACGIH
2,2'-iminodiethanol	111-42-2	TWA	2 mg/m3	CA AB OEL

sion 3.1	Revision I	Revision Date 10/01/2023		Print Date 08/06/2024	
	I	TWA	2 mg/m3	CA BC OI	
		TWAEV	3 ppm 13 mg/m3	CA QC O	
		TWA (Inhalable fraction and vapor)	1 mg/m3	ACGIH	
Engineering measures	: effective ve	entilation in all pro	cessing areas		
Personal protective equip	nent				
Respiratory protection	ventilation	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.			
Hand protection Material	: Protective	gloves			
Remarks		The suitability for a specific workplace should be discussed with the producers of the protective gloves.			
Eye protection	Access to include: ey	Tightly fitting safety goggles Access to clean water to rinse eyes must be available, options include: eye wash stations or showers, or eye wash bottles with pure water.			
Skin and body protection	Choose bo	Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.			
Hygiene measures	When usin	g do not eat or dri g do not smoke. s before breaks	nk. and at the end o	f workday.	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Aerosol containing a liquefied gas
Colour	: amber
Odour	: characteristic
Odour Threshold	: No data available
рH	: 11.5
Melting point/freezing point	: Not applicable
Boiling point	: No data available
Flash point	: Not applicable
Evaporation rate	: No data available
Flammability (solid, gas, liquid)	: Extremely flammable aerosol.

Revision Date 10/01/2023 Print Date 08/06/2024

Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Density	: 1.012 g/cm3
Solubility(ies)	
Water solubility	: partly soluble
Partition coefficient: n- octanol/water	: No data available
Auto-ignition temperature	: not determined
Thermal decomposition	: No data available
Viscosity	
Viscosity, kinematic	: No data available
Heat of combustion	: > 30 kJ/g

Version 3.1

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Stable
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	:	Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	:	Strong oxidizing agents
Hazardous decomposition products	:	Carbon oxides Phosphorus compounds Sulphur oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects		
Aggravated Medical Condition	:	None known.
Symptoms of Overexposure	:	Chronic effects are delayed and symptoms may not be observed during an exposure. Effects are dependent on exposure (dose, concentration,

Version 3.1	Revision Date 10/01/2023	Print Date 08/06/2024
	contact time). Effects are immediate and delayed. Symptoms may include irritation, redne Causes serious eye irritation. May cause an allergic skin reaction. Review section 2 of SDS to see all pote Causes skin irritation. Treat symptomatically. Symptoms may	ential hazards.
Carcinogenicity:		
IARC	Group 2B: Possibly carcinogenic to human	ns
	Amides, coco, N,N- bis(hydroxyethyl)	68603-42-9
	2,2'-iminodiethanol	111-42-2
ACGIH	Confirmed animal carcinogen with unknov humans	wn relevance to
	2,2'-iminodiethanol	111-42-2
Acute toxicity		
Product:		
Acute oral toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method	I
Acute inhalation toxicity	: Acute toxicity estimate : > 10 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method	
Acute dermal toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method	I
Components:		
sodium dodecylbenzenesu Acute oral toxicity	Ifonate: : LD50 Oral Rat: 438 mg/kg	
d-limonene: Acute oral toxicity	: LD50 Oral Rat: 4,400 mg/kg	
Acute dermal toxicity	: LD50 Dermal Rabbit: > 5,000 mg/kg	
benzyl alcohol: Acute dermal toxicity	: LD50 Rabbit: 1,250 mg/kg	
Skin corrosion/irritation		
Product:		

Version 3.1

Revision Date 10/01/2023

Print Date 08/06/2024

Remarks: Irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks: Irritating to eyes.

Respiratory or skin sensitisation

Product:

Remarks: Causes sensitisation.

Components:

d-limonene:

Classification: May cause sensitisation by skin contact.

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

<u>Components:</u> Amides, coco, N,N-bis(hydroxyethyl): Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Print Date 08/06/2024 Version 3.1 Revision Date 10/01/2023 No data available Persistence and degradability No data available **Bioaccumulative potential** Product: : Remarks: No data available Partition coefficient: noctanol/water Components: 2-(2-butoxyethoxy)ethanol : Partition coefficient: n-: Pow: 1 octanol/water d-limonene : Partition coefficient: n-: log Pow: 4.232 octanol/water butane : Partition coefficient: n-: Pow: 2.89 octanol/water Amides, coco, N,N-bis(hydroxyethyl) : Partition coefficient: n-: Remarks: No data available octanol/water benzyl alcohol: Partition coefficient: n-: log Pow: 1.05 (20 °C) octanol/water 2,2'-iminodiethanol : Partition coefficient: n-: Pow: 1.43 octanol/water Mobility in soil No data available Other adverse effects No data available **Product:** Additional ecological : An environmental hazard cannot be excluded in the information event of unprofessional handling or disposal., Toxic to aquatic life. The GHS H401 statement "Toxic to aquatic life" noted above is an Acute Aquatic Toxicity Category 2 classification. Although the product has the potential to harm the environment, it is not classified as a marine pollutant or regulated under transportation regulations. **Components:** Amides, coco, N,N-bis(hydroxyethyl) : : No data available Additional ecological information

SECTION 13. DISPOSAL CONSIDERATIONS

Version 3.1	Revision Date 10/01/2023	Print Date 08/06/2024
Disposal methods		
Waste from residues	 The product should not be allowed to courses or the soil. Do not contaminate ponds, waterway chemical or used container. Dispose of in accordance with local r 	s or ditches with
Contaminated packaging	 Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch or 	n, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation (TDG) / Règlement Pour Le Transport (TMD): (Canada): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IMDG (Vessel): UN1950, AEROSOLS, 2.2, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IATA (Cargo Air): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IATA (Passenger Air): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: 49 CFR (USA): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under Transport Dangerous Goods (TDG) Canada regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

The components of this product are reported in the following inventories:

DSL	All components of this product are on the Canadian DSL
TSCA	On TSCA Inventory

Version 3.1

Revision Date 10/01/2023


Print Date 08/06/2024

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)





Version:	3.1
Revision Date:	10/01/2023
Print Date:	08/06/2024

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.