Version 2.1 Revision Date 10/01/2023 Print Date 08/06/2024

#### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

ZEP 40 NON-STREAKING CLEANER 20N18 12CT Material name

Material number 00000000000014411

#### Manufacturer or supplier's details

Company : Zep Inc.

Address 11627 - 178 Street

Edmonton, Alberta T5S 1N6

Canada

Telephone : Compliance Services - 877-428-9937

# **Emergency telephone numbers**

For SDS Information Compliance Services - 877-428-9937

877-541-2016 Toll Free - All Calls Recorded For a Medical Emergency

CHEMTREC: 800-424-9300 - All Calls Recorded. For a Transportation

**Emergency** 

Recommended use of the chemical and restrictions on use

#### **SECTION 2. HAZARDS IDENTIFICATION**

#### **Emergency Overview**

| Appearance | Aerosol containing a liquefied gas |  |  |
|------------|------------------------------------|--|--|
| Colour     | colourless, clear                  |  |  |
| Odour      | alcohol-like, slight               |  |  |

#### **GHS Classification**

Gases under pressure : Liquefied gas Eye irritation : Category 2A

#### **GHS** label elements

Hazard pictograms



Gas cy linder

Exclamation mark

Signal word : Warning

Hazard statements : H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

Version 2.1 Revision Date 10/01/2023 Print Date 08/06/2024

Precautionary statements : **Prevention:** 

P264 Wash skin thoroughly after handling. P280 Wear eye protection/ face protection.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/

attention. Storage:

P403 Store in a well-ventilated place.

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

#### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### **Hazardous components**

| Chemical name   | CAS-No.  | Concentration [%] |
|-----------------|----------|-------------------|
| ethanol         | 64-17-5  | >= 10 - < 30      |
| butane          | 106-97-8 | >= 1 - < 5        |
| 2-butoxyethanol | 111-76-2 | >= 1 - < 5        |
| propane         | 74-98-6  | >= 1 - < 5        |

### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Wash off immediately with plenty of water for at least 15

minutes.

If skin irritation persists, call a physician.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist. If in eyes, rinse with water for 15 minutes.

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

Version 2.1 Revision Date 10/01/2023 Print Date 08/06/2024

Most important symptoms and effects, both acute and

delayed

: Effects are immediate and delayed.

Symptoms may include irritation, redness, pain, and rash.

Causes serious eye irritation.

Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Water spray jet

Carbon dioxide (CO2) Alcohol-resistant foam

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2)

Carbon monoxide

Smoke

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Ensure adequate ventilation.

Refer to protective measures listed in sections 7 and 8. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Sweep up or vacuum up spillage and collect in suitable

container for disposal.

Version 2.1 Revision Date 10/01/2023 Print Date 08/06/2024

#### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Avoid contact with skin and eyes.

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Always replace cap after use.

Dispose of rinse water in accordance with local and national

regulations.

Avoid exposure - obtain special instructions before use. Take precautionary measures against static discharges.

Do not breathe vapours or spray mist.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects.

Observe label precautions.

Keep in a dry, cool and well-ventilated place.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Do not freeze.

Strong oxidizing agents

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# Components with workplace control parameters

| Components      | CAS-No.  | Value type<br>(Form of<br>exposure) | Control parameters / Permissible concentration | Basis     |
|-----------------|----------|-------------------------------------|--|-----------|
| ethanol         | 64-17-5  | TWA 1,000 ppm CA 1,880 mg/m3        |  | CA AB OEL |
|                 |          | STEL                                | 1,000 ppm                                      | CA BC OEL |
|                 |          | TWAEV                               | 1,000 ppm<br>1,880 mg/m3                       | CA QC OEL |
|                 |          | TWA                                 | 1,000 ppm                                      | ACGIH     |
|                 |          | STEL                                | 1,000 ppm                                      | ACGIH     |
| butane          | 106-97-8 | TWA                                 | 1,000 ppm                                      | CA AB OEL |
|                 |          | TWA                                 | 600 ppm  | CA BC OEL |
|                 |          | STEL                                | 750 ppm  | CA BC OEL |
|                 |          | TWAEV                               | 800 ppm<br>1,900 mg/m3                         | CA QC OEL |
|                 |          | STEL                                | 1,000 ppm                                      | ACGIH     |
| 2-butoxyethanol | 111-76-2 | TWA                                 | 20 ppm<br>97 mg/m3                             | CA AB OEL |
|                 |          | TWA                                 | 20 ppm   | CA BC OEL |
|                 |          | TWAEV                               | 20 ppm<br>97 mg/m3                             | CA QC OEL |
|                 |          | TWA                                 | 20 ppm   | ACGIH     |
| propane         | 74-98-6  | TWA                                 | 1,000 ppm                                      | CA AB OEL |
|                 |          | TWA                                 | 1,000 ppm                                      | CA BC OEL |

Version 2.1 Revision Date 10/01/2023 Print Date 08/06/2024

| TWAEV | · ·                      | CA QC OEL |
|-------|--------------------------|-----------|
| TWA   | 1,800 mg/m3<br>1,000 ppm | CA ON OEL |

#### Biological occupational exposure limits

| Components      | CAS-No.  | Control parameters             | Biological specimen | Samplin<br>g time  | Permissible concentratio n | Basis        |
|-----------------|----------|--------------------------------|---------------------|--|----------------------------|--------------|
| 2-BUTOXYETHANOL | 111-76-2 | Butoxyaceti<br>c acid<br>(BAA) | Urine               | End of<br>shift (As<br>soon as<br>possible<br>after<br>exposure<br>ceases) | 200 mg/g<br>Creatinine     | ACGIH<br>BEI |

**Engineering measures** : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Tightly fitting safety goggles

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work

place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a liquefied gas

Colour : colourless, clear
Odour : alcohol-like, slight
Odour Threshold : No data available

pH : 10.5 - 11.5

Melting point/freezing point : Not applicable

Boiling point : Not applicable

Flash point :

Version 2.1 Revision Date 10/01/2023 Print Date 08/06/2024

Not applicable

Evaporation rate : 1

n-Butyl Acetate = 1.0

Flammability (solid, gas,

Relative vapour density

liquid)

: The product is not flammable.

Upper explosion limit : Not applicable
Lower explosion limit : Not applicable
Vapour pressure : No data available

Density : 1.1 g/cm3

Solubility(ies)

Water solubility : soluble

Solubility in other solvents : not determined

Partition coefficient: n-

octanol/water

: No data available

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : Not applicable Heat of combustion : 7.94 kJ/g

# **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: Vapours may form explosive mixture with air.

No decomposition if stored and applied as directed.

Conditions to avoid : Heat, flames and sparks.

Extremes of temperature and direct sunlight.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

: Carbon monoxide, carbon dioxide and unburned

hydrocarbons (smoke).

## **SECTION 11. TOXICOLOGICAL INFORMATION**

Version 2.1 Revision Date 10/01/2023 Print Date 08/06/2024

**Potential Health Effects** 

Aggravated Medical

Condition

: None known.

Symptoms of Overexposure : Effects are immediate and delayed.

Symptoms may include irritation, redness, pain, and rash.

Causes serious eye irritation.

Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH Confirmed animal carcinogen with unknown relevance to

humans

ethanol 64-17-5

2-butoxyethanol 111-76-2

Acute toxicity

**Product:** 

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : > 10 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Components:

ethanol:

Acute oral toxicity : LD50 Oral Rat: 7,060 mg/kg

Acute inhalation toxicity : LC50 Rat: 124.7 mg/l

Exposure time: 4 h
Test atmosphere: vapour

2-butoxyethanol:

Acute oral toxicity : LD50 Oral Rat: 880 mg/kg

Acute dermal toxicity : LD50 Dermal Rabbit: 1,060 mg/kg

Skin corrosion/irritation

Version 2.1 Revision Date 10/01/2023 Print Date 08/06/2024

**Product:** 

Remarks: May cause skin irritation and/or dermatitis.

### Serious eye damage/eye irritation

**Product:** 

Remarks: Severe eye irritation

# Respiratory or skin sensitisation

No data available

### Germ cell mutagenicity

No data available

# Carcinogenicity

No data available

## Reproductive toxicity

No data available

# STOT - single exposure

No data available

#### STOT - repeated exposure

No data available

# Aspiration toxicity

No data available

#### **Further information**

### **Product:**

Remarks: No data available

#### **SECTION 12. ECOLOGICAL INFORMATION**

# **Ecotoxicity**

No data available

### Persistence and degradability

No data available

# Bioaccumulative potential

#### **Product:**

Partition coefficient: noctanol/water

Components: ethanol :

Partition coefficient: n- : Remarks: No data available

Version 2.1 Revision Date 10/01/2023 Print Date 08/06/2024

: Remarks: No data available

Partition coefficient: n-

octanol/water

butane :

Partition coefficient: n-

octanol/water

: Pow: 2.89

Mobility in soil

No data available

Other adverse effects

No data available

**Product:** 

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to

aquatic life.

### **SECTION 13. DISPOSAL CONSIDERATIONS**

Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

#### **SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation (TDG) / Règlement Pour Le Transport (TMD): (Canada): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IMDG (Vessel): UN1950, AEROSOLS, 2.2, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IATA (Cargo Air): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IATA (Passenger Air): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: 49 CFR (USA): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under Transport Dangerous Goods (TDG) Canada regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

Version 2.1 Revision Date 10/01/2023 Print Date 08/06/2024

#### **SECTION 15. REGULATORY INFORMATION**

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

The components of this product are reported in the following inventories:

DSL All components of this product are on the Canadian DSL

TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

### **Inventory Acronym and Validity Area Legend:**

TSCA (USA), DSL (Canada), NDSL (Canada)

#### **SECTION 16. OTHER INFORMATION**

### WHMIS - GHS Label Information:

Hazard pictograms



Exclamation

mark

Signal w ord Hazard statements Precautionary statements

Warning:

Contains gas under pressure; may explode if heated. Causes serious eye irritation.

**Prevention:** Wash skin thoroughly after handling. Wear eye protection/face protection. **Response:** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

**Storage:** Store in a w ell-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

| Version:       | 2.1        |
|----------------|------------|
| Revision Date: | 10/01/2023 |
| Print Date:    | 08/06/2024 |

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it

Version 2.1 Revision Date 10/01/2023 Print Date 08/06/2024

is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.