Version 2.2

Revision Date 10/01/2023

Print Date 08/06/2024

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name	:	ZEP ZEPRESERVE
Material number	:	00000000000143485
Manufacturer or supplier's d	eta	ils
Company	:	Zep Inc.
Address	:	350 Joe Frank Harris Parkway, SE Emerson, GA 30137
Telephone	:	Compliance Services - 877-428-9937

Emergency telephone nu	mbe	rs
For SDS Information	:	Compliance Services - 877-428-9937
For a Medical Emergency	:	877-541-2016 Toll Free - All Calls Recorded
For a Transportation	:	CHEMTREC: 800-424-9300 - All Calls Recorded.
Emergency		In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

### SECTION 2. HAZARDS IDENTIFICATION

#### Emergency Overview

Appearance	liquid
Colour	dark brown
Odour	sweet

### **GHS Classification**

Flammable liquids Eye irritation Aspiration hazard	: Category 3 : Category 2A : Category 1
GHS label elements	
Hazard pictograms	: Flame Health hazard Exclamation mark
Signal word	: Danger
Hazard statements	<ul> <li>H226 Flammable liquid and vapour.</li> <li>H304 May be fatal if swallowed and enters airways.</li> <li>H319 Causes serious eye irritation.</li> </ul>
Precautionary statements	<ul> <li>Prevention:</li> <li>P210 Keep away from heat/sparks/open flames/hot surfaces.</li> <li>No smoking.</li> <li>P233 Keep container tightly closed.</li> </ul>

Version 2.2	Revision Date 10/01/2023	Print Date 08/06/2024
	<ul> <li>P240 Ground/bond container an P241 Use explosion-proof electrequipment.</li> <li>P242 Use only non-sparking too P243 Take precautionary measu P264 Wash skin thoroughly after P280 Wear protective gloves/ ey <b>Response:</b></li> <li>P301 + P310 IF SWALLOWED: CENTER/doctor.</li> <li>P303 + P361 + P353 IF ON SKI immediately all contaminated clowater/shower.</li> <li>P305 + P351 + P338 IF IN EYES for several minutes. Remove coneasy to do. Continue rinsing.</li> <li>P331 Do NOT induce vomiting.</li> <li>P337 + P313 If eye irritation personattention.</li> <li>P370 + P378 In case of fire: Use alcohol-resistant foam to extinguistication.</li> <li>P403 + P235 Store in a well-vention.</li> <li>P501 Dispose of contents/contained regulation.</li> </ul>	rical/ ventilating/ lighting ols. ures against static discharge. r handling. ye protection/ face protection. Immediately call a POISON IN (or hair): Take off othing. Rinse skin with S: Rinse cautiously with water ntact lenses, if present and sists: Get medical advice/ e dry sand, dry chemical or uish. tilated place. Keep cool.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Hazardous components

Chemical name	CAS-No.	Concentration [%]
Distillates (petroleum), hydrotreated light	64742-47-8	>= 50 - < 70
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 20 - < 30
2-ethylhexan-1-ol	104-76-7	>= 5 - < 10
2-(2-butoxyethoxy)ethanol	112-34-5	>= 5 - < 10

The exact percentages of disclosed substances are withheld as trade secrets.

#### **SECTION 4. FIRST AID MEASURES**

General advice	<ul> <li>Move out of dangerous area.</li> <li>Show this safety data sheet to the doctor in attendance.</li> <li>Symptoms of poisoning may appear several hours later.</li> <li>Do not leave the victim unattended.</li> </ul>
If inhaled	<ul> <li>If unconscious, place in recovery position and seek medical advice.</li> <li>If symptoms persist, call a physician.</li> </ul>

Version 2.2	Revision Date 10/01/2023	Print Date 08/06/2024
In case of skin contact	<ul> <li>Wash off immediately with plenty o minutes.</li> <li>Remove contaminated clothing and Wash contaminated clothing before If skin irritation persists, call a physical</li> </ul>	d shoes. e reuse.
In case of eye contact	: Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a s In case of contact, immediately flus for at least 15 minutes.	
If swallowed	<ul> <li>Keep respiratory tract clear.</li> <li>Do NOT induce vomiting.</li> <li>Do not give milk or alcoholic bevera Never give anything by mouth to an If symptoms persist, call a physicia Take victim immediately to hospital</li> </ul>	n unconscious person. n.
Most important symptoms and effects, both acute and delayed	<ul> <li>Effects are immediate and delayed Effects are dependent on exposure contact time).</li> <li>Symptoms may include irritation, re Symptoms may include shortness of irritation of the nose, eyes, lips, mod Aspiration may cause pulmonary o May be fatal if swallowed and enter Causes serious eye irritation.</li> <li>Review section 2 of SDS to see all</li> </ul>	e (dose, concentration, edness, pain, and rash. of breath, dry cough, and outh, and throat. edema and pneumonitis. rs airways.
Notes to physician	: Treat symptomatically. Symptoms	may be delayed.

### SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	Carbon dioxide (CO2) Carbon monoxide Smoke
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must

Version 2.2	Revision Date 10/01/2023	Print Date 08/06/2024
	be disposed of in accordance with For safety reasons in case of fire, separately in closed containments Use a water spray to cool fully clo	cans should be stored
Special protective equipment for firefighters	: Wear self-contained breathing ap necessary.	paratus for firefighting if

## SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains, inform respective authorities.
Methods and materials for containment and cleaning up	:	Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### SECTION 7. HANDLING AND STORAGE

Advice on safe handling	:	Avoid formation of aerosol. Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
Conditions for safe storage	:	No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
Materials to avoid	:	Keep away from oxidizing agents and strongly acid or alkaline materials.

Version 2.2

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
		PEL (particulate)	5 mg/m3	CAL PEL
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m3	ACGIH
2-(2-butoxyethoxy)ethanol	112-34-5	TWA (Inhalable fraction and vapor)	10 ppm	ACGIH

Engineering measures	: effective ventilation in all processing areas
----------------------	---

Personal protective equipme		
Respiratory protection	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrate that exposures are within recommended exposure guideline	
Hand protection		
Material	Protective gloves	
Remarks	The suitability for a specific workplace should be discussed with the producers of the protective gloves.	
Eye protection	Tightly fitting safety goggles Wear face-shield and protective suit for abnormal processing problems.	-
	Ensure that eyewash stations and safety showers are close the workstation location.	το
Skin and body protection	Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place	<u>)</u> _
Hygiene measures	When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.	

Version 2.2

Revision Date 10/01/2023

Print Date 08/06/2024

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES		
Appearance	: liquid	
Colour	: dark brown	
Odour	: sweet	
Odour Threshold	: No data available	
рН	: No data available	
Melting point/freezing point	: No data available	
Boiling point	: 151.7 °C	
Flash point	: 39.4 °C Method: closed cup	
Evaporation rate	: 0.1	
Upper explosion limit	: No data available	
Lower explosion limit	: No data available	
Vapour pressure	: No data available	
Relative vapour density	: No data available	
Density	: 0.826 g/cm3	
Bulk density	: No data available	
Solubility(ies)		
Water solubility	: insoluble	
Solubility in other solvents	: insoluble	
Partition coefficient: n- octanol/water	: No data available	
Auto-ignition temperature	: not determined	
Thermal decomposition	: No data available	
Viscosity		
Viscosity, dynamic	: No data available	
Viscosity, kinematic	: 7 mm2/s (20 °C)	

### SECTION 10. STABILITY AND REACTIVITY

Reactivity

: Stable

Version 2.2	Revision Date 10/01/2023	Print Date 08/06/2024
Chemical stability	: Stable under normal conditions.	
Possibility of hazardous reactions	: No decomposition if stored and app	lied as directed.
	Vapours may form explosive mixtur	e with air.
Conditions to avoid	: Heat, flames and sparks.	
Incompatible materials	: Oxidizing agents	
Hazardous decomposition products	: Carbon oxides Sulphur oxides	

### SECTION 11. TOXICOLOGICAL INFORMATION

### **Potential Health Effects**

Aggravated Medical Condition	: None known.
Symptoms of Overexposure	<ul> <li>Effects are immediate and delayed.</li> <li>Effects are dependent on exposure (dose, concentration, contact time).</li> <li>Symptoms may include irritation, redness, pain, and rash.</li> <li>Symptoms may include shortness of breath, dry cough, and irritation of the nose, eyes, lips, mouth, and throat.</li> <li>Aspiration may cause pulmonary oedema and pneumonitis.</li> <li>May be fatal if swallowed and enters airways.</li> <li>Causes serious eye irritation.</li> <li>Review section 2 of SDS to see all potential hazards.</li> <li>Treat symptomatically. Symptoms may be delayed.</li> </ul>
Carcinogenicity:	
IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
Acute toxicity	
Product:	
Acute oral toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method
Acute dermal toxicity	: Acute toxicity estimate : > 5,000 mg/kg

Version 2.2

## Revision Date 10/01/2023

Print Date 08/06/2024

### Method: Calculation method

Components:	
Distillates (petroleum), hydro	
Acute oral toxicity	: LD50 Rat: > 5,000 mg/kg
Acute inhalation toxicity	: LC50 Rat: > 4.6 mg/l Exposure time: 6 h
Acute dermal toxicity	: LD50 Rat: > 2,000 mg/kg
<b>Distillates (petroleum), hydro</b> Acute oral toxicity	otreated heavy naphthenic: : LD50 Rat: > 5,000 mg/kg
Acute inhalation toxicity	: LC50 Rat: > 5 mg/l Exposure time: 4 h
Acute dermal toxicity	: LD50 Rabbit: > 5,000 mg/kg
<b>2-ethylhexan-1-ol:</b> Acute oral toxicity	: LD50 Oral Rat: 3,730 mg/kg
Acute dermal toxicity	: LD50 Dermal Rabbit: > 3,000 mg/kg
Skin corrosion/irritation	
Product:	
Remarks: Irritating to skin.	
Serious eye damage/eye irritatio	n
Product:	
Remarks: Irritating to eyes.	
Respiratory or skin sensitisation	
No data available	
Germ cell mutagenicity	
No data available	
Carcinogenicity	
No data available	
Reproductive toxicity	
No data available	
STOT - single exposure	
No data available	

### STOT - repeated exposure

Version 2.2

Revision Date 10/01/2023

Print Date 08/06/2024

No data available

### Aspiration toxicity

No data available

### **Further information**

### Product:

Remarks: Solvents may degrease the skin.

### SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

No data available

### Persistence and degradability

### No data available Bioaccumulative potential

•		
Product:		
Partition coeffici octanol/water	ent: n- :	Remarks: No data available
<u>Components:</u> 2-ethylhexan-1-o	1:	
Partition coeffici octanol/water	ent: n- :	Pow: 2.9
2-(2-butoxyethox	• •	David 4
Partition coeffici octanol/water	ent: n- :	Pow: 1
Mobility in soil		
No data available		
Other adverse effects	<b>i</b>	
No data available <u>Product:</u>		
Regulation		40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks		This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).
Additional ecolo information	gical :	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life with long lasting effects.

Version 2.2

Revision Date 10/01/2023

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

Disposal methods	
Waste from residues	<ul> <li>The product should not be allowed to enter drains, water courses or the soil.</li> <li>Do not contaminate ponds, waterways or ditches with chemical or used container.</li> <li>Dispose of in accordance with local regulations.</li> </ul>
Contaminated packaging	<ul> <li>Empty remaining contents.</li> <li>Dispose of as unused product.</li> <li>Do not re-use empty containers.</li> <li>Do not burn, or use a cutting torch on, the empty drum.</li> </ul>

#### SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IMDG (Vessel): UN1993, FLAMMABLE LIQUID, N.O.S., (PETROLEUM DISTILLATES), 3, III

Transportation Regulation: IATA (Cargo Air): UN1993, Flammable liquid, n.o.s., (PETROLEUM DISTILLATES), 3, III

Transportation Regulation: IATA (Passenger Air): UN1993, Flammable liquid, n.o.s., (PETROLEUM DISTILLATES), 3, III

Transportation Regulation: TDG (Canada): NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

### SECTION 15. REGULATORY INFORMATION

TSCA list

: No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Version 2.2

Revision Date 10/01/2023

This material does not contain any components with a CERCLA RQ.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards	: Flammable (gases, aerosols, liquids Serious eye damage or eye irritation Aspiration hazard	,
SARA 302	: No chemicals in this material are sur requirements of SARA Title III, Sect	
SARA 313	: The following components are subjected by SARA Title III, Section 2-(2-butoxyethoxy)ethanol 2-butoxyethanol	
California Prop. 65		
	This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other	

reproductive harm.

## The components of this product are reported in the following inventories:

DSL	All components of this product are on the Canadian DSL
TSCA	On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

#### Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

**SECTION 16. OTHER INFORMATION** 

Version 2.2

Revision Date 10/01/2023

Print Date 08/06/2024

### **Further information**

#### NFPA:



0 = not significant, 1 = Slight,

2 = Moderate, 3 = High


4 = Extreme

#### HMIS III:

HEALTH	3
FLAMMABILITY	2
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

- 2 = Moderate, 3 = High
- 4 = Extreme, \* = Chronic



Version 2.2

#### Revision Date 10/01/2023

Print Date 08/06/2024

**Storage :** Store in a w ell-ventilated place. Keep cool. **Disposal :** Dispose of contents/container in accordance with local regulation.

Version:	2.2
Revision Date:	10/01/2023
Print Date:	08/06/2024

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.